



































		2L	5L
cm ³ or CC (cu. in.)		2446 (149.3)	2986 (182.2)
 mm (in.)		10–14 (0.39–0.55) ※196–343 (20–35)	
		15–21 (0.59–0.83) ※392–588 (40–60)	
		9–13 (0.35–0.51) ※196–343 (20–35)	
 20°C (68°F) Ω		0.72	
 20°C (68°F) secs		Turkey 3 Others 5	※1 3 Others 5
 mm (in.)		w/ ACSD 0.44–0.56 (0.0173–0.0220) w/o ACSD 0.84–0.96 (0.0331–0.0378) Turkey 0.54–0.66 (0.0212–0.0260)	w/ ACSD ※ 2 0.64–0.76 (0.0252–0.0299) ※ 3 0.44–0.56 (0.0173–0.0220) w/o ACSD 0.64–0.76 (0.0252–0.0299)
			
 kPa (kgf/cm ² , psi)		14220–15200 (145–155, 2062–2205)	15090–16290 (154–166, 2190–2361)
 mm (in.)		14810–15590 (151–159, 2148–2262)	15581–16781 (159–171, 2262–2432)
 mm (in.)		0.20–0.30 (0.008–0.012)	
 mm (in.)		0.40–0.50 (0.016–0.020)	

 rpm		650–750	
		4770–5030	
 kPa (kgf/cm ² , psi)		3138 (32.0, 455)	
		1961 (20.0, 284)	
 N·m (kgf-cm, ft-lbf)		490 (5.0, 71)	
		78 (800, 58)	
 kPa (kgf/cm ² , psi)		23.5 (240, 17)	
		52 (530, 38)	
 kPa (kgf/cm ² , psi)		64 (650, 47)	
		29.5 (300, 22)	
 kPa (kgf/cm ² , psi)		29 (0.3, 4.3)	
		294–539 (3.0–5.5, 43–78)	

		LH	
 liter (US qts, Imp. qts)		5.1 (5.4, 4.5)	
		6.0 (6.3, 5.3)	
 liter (US qts, Imp. qts)	API CF-4 or CF (You may also use API CE or API CD)		
	w/ Front and Rear Heaters 11.0 (11.6, 9.7)		
	w/ Front Heater 9.5 (10.0, 8.4)		
	w/o Heater 8.5 (9.0, 7.5)		

Hiace Diesel

LH102 - 0080540~ LH104 - 0010004~ LH112 - 0094540~ LH114 - 0034676~, 7006457~ LH154 - 0001008~, 1000002~
 LH162 - 0011995~, 1000010~ LH164 - 0001002~ LH166 - 0001060~ LH172 - 1000223~, 6101311~
 LH174 - 0004860~, 8000001~, 1000002~ LH176 - 0001039~ LH184 - 1003132~



		LH
	A	170 (6.69)
	B	5-15 (0.20-0.59)
	C	25 (0.98)
mm (in.)		SAE J1703 or FMVSS No. 116 DOT3

		LH
	A	151.5 (5.965)
	B	1-6 (0.04-0.24)
	C	58 (2.28)
mm (in.)		SAE J1703 or FMVSS No. 116 DOT3

196 N (20 kgf, 44.1 lbf)		18-24
		5-7

	A	1.0 (0.039)
	B	14 in. 23.0 (0.906) 15 in. 26.0 (1.024)
mm (in.)		

	1.0 (0.039)
mm (in.)	

	4×2	272 (10.709)
	4×4	297 (11.693)
	mm (in.)	

		LH
	(4×2) A+[5.9-18] (0.6-1.8 1.3-4.0)	
	(4×4) A+[19-47] (1.9-4.8 4.2-9.6)	
N (kgf·m lbf)		
		103 (1050, 76)
N·m (kgf·cm, ft·lbf)		







		LH
	2WD	2.2 (2.3, 1.9)
	4WD	2.6 (2.7, 2.3)
liter (US qts, Imp. qts)		API GL-4 or GL-5 SAE 75 W-90




		2.4 (2.5, 2.1)
liter (US qts, Imp. qts)		ATF DII or DEXRON® III (DEXRON® II)

		1.3 (1.4, 1.1)
liter (US qts, Imp. qts)		API GL-4 or GL-5 SAE 75W-90

		1.35 (1.4 1.2)	2.2 (2.3 1.9)
liter (US qts, Imp. qts)		Hypoid gear oil API GL-5 With LSD use LSD oil only SAE90 (18°C (0°F)) SAE80W or 80W-90 (-18°C (0°F))	

		LH
		40 (1.57)
mm (in.)		

		2WD	4WD
   ※  Bias Tire	A	Please refer to the Service Bulletin Ref. No. CP-0017	$0^{\circ}00' \pm 30'$ $(0.00^{\circ} \pm 0.5^{\circ})$
	B		$12^{\circ}35' \pm 30'$ $(12.58^{\circ} \pm 0.5^{\circ})$
	C		$2^{\circ}55' \pm 30'$ $(2.92^{\circ} \pm 0.5^{\circ})$
	D		$30^{\circ} \begin{smallmatrix} +0^{\circ} \\ -3^{\circ} \end{smallmatrix}$ $(30^{\circ} \begin{smallmatrix} +0^{\circ} \\ -3^{\circ} \end{smallmatrix})$
	E+F		$0^{\circ}00' \pm 6'$ $(0^{\circ} \pm 0.1^{\circ})$
	G-H mm (in.)		0 ± 1 (0 ± 0.04)

				
 kPa (<i>kgf/cm² or bar, psi</i>)	Australia	185R14C	325 (3.25, 47)	450 (4.50, 65)
		195/70R15C	325 (3.25, 47)	425 (4.25, 62)
	Others	Please refer to the Owner's Manual. (Part 8. SPECIFICATIONS)		