
































				2L	5L	5L-E
cm <sup>3</sup> or CC (cu. in.)				2446 (149.3)	2986 (182.2)	
 mm (in.)	 N (kgf)		10–14 (0.39–0.55) ※196–343 (20–35)			
			15–21 (0.59–0.83) ※392–588 (40–60)			
			9–13 (0.35–0.51) ※196–343 (20–35)			
 20°C (68°F) Ω		0.72				
 20°C (68°F) secs		5	※ 1 3 Others 5	3		
 mm (in.)		w/ ACSD 0.44–0.56 (0.0173–0.0220) w/ o ACSD 0.84–0.96 (0.0331–0.0378) Turkey 0.54–0.66 (0.0212–0.0260)	w/ ACSD (w/ o HAC) 0.44–0.56 (0.0173–0.0220) Others 0.64–0.76 (0.0252–0.0299)	—		
						
 kPa (kgf/cm <sup>2</sup> , psi)		14220–15200 (145–155, 2062–2205)	15090–16290 (154–166, 2190–2361)			
 mm (in.)		14810–15590 (151–159, 2148–2262)	15581–16781 (159–171, 2262–2432)			
 mm (in.)			0.20–0.30 (0.008–0.012)			
			0.40–0.50 (0.016–0.020)			

 rpm	 	650-750		
	 	Malaysia 4570-4830 Others 4770-5030	750-850	4750-5050
 kPa (kgf/cm <sup>2</sup> , psi)		3138 (32.0, 455)		
		1961 (20.0, 284)		
		490 (5.0, 71)		
 N·m (kgf-cm, ft-lbf)	A	 ① 78 (800, 58) ② 90° ③ 90°		
	B	23.5 (240, 17)		
	C	52 (530, 38)		
	D	64 (650, 47)		
	E	29.5 (300, 22)		
 kPa (kgf/cm <sup>2</sup> , psi)	 3,000 rpm	29 (0.3, 4.3)		
		294-539 (3.0-5.5, 43-78)		

		LH		
 liter (US qts, Imp. qts)		5.1 (5.4, 4.5)		
 liter (US qts, Imp. qts)		6.0 (6.3, 5.3)		
 liter (US qts, Imp. qts)		API CF-4, CF or G-DLD-1 (You may also use API CE or CD)		
 liter (US qts, Imp. qts)		w/ Front and Rear Heaters 11.0 (11.6, 9.7) w/ Front Heater 9.5 (10.0, 8.4) w/o Heater 8.5 (9.0, 7.5)		

# Hiace Diesel

LH102 - 6009462~ LH104 - 6000452~ LH112 - 4000115~, 7013040~ LH114 - 4000913~, 5000105~, 7012927~ LH154 - 1002985~  
 LH162 - 1009638~ LH164 - 1000145~ LH166 - 1000085~ LH168 - 1001915~ LH172 - 1035181~, 5000540~, 6116131~  
 LH174 - 1012977~, 7000100~, 8000930~ LH176 - 1000123~ LH178 - 7006955~ LH184 - 1016112~



		LH
	A	170 (6.69)
	B	5-15 (0.20-0.6)
	C	25 (0.98)
mm (in.)		SAE J1703 or FMVSS No. 116 DOT3

		LH
	A	151.5 (5.965)
	B	1-6 (0.04-0.24)
	C*1	58 (2.28)
mm (in.)		SAE J1703 or FMVSS No. 116 DOT3

196 N (20 kgf, 44.1 lbf)		18-24
		5-7

	A	1.0 (0.039)
	B	14 in. 23.0 (0.906) 15 in. 26.0 (1.024)
mm (in.)		

	1.0 (0.039)
mm (in.)	

	4×2	272 (10.709)
	4×4	297 (11.693)
	mm (in.)	

		LH
	(4×2) A+[5.9-18] (0.6-1.8 1.3-4.0)	
	(4×4) A+[19-47] (1.9-4.8 4.2-9.6)	
N (kgf·m lbf)		
	100 (1020, 74)	
N·m (kgf·cm, ft·lbf)		

		LH
	2WD 2.2 (2.3, 1.9)	
	4WD 2.6 (2.7, 2.3)	
liter (US qts, Imp. qts)		API GL-4 or GL-5 SAE 75 W-90

	2.4 (2.5, 2.1)
liter (US qts, Imp. qts)	Toyota Genuine ATF DII or DEXRON®III (DEXRON®II)

	1.3 (1.4, 1.1)
liter (US qts, Imp. qts)	API GL-4 or GL-5 SAE 75W-90

	1.35 (1.4 1.2)	2.2 (2.3 1.9)
	Hypoid gear oil API GL-5 With LSD use LSD oil only SAE90 (1) -18°C (0°F) SAE80W or 80W-90 (2) -18°C (0°F)	
liter (US qts, Imp. qts)		

		LH
	40 (1.6)	
mm (in.)		

		2WD	4WD
	A	Please refer to the Service Bulletin Australia Ref. No. CP-2013 Others Ref. No. CP-0017	0°05'±30' (0.08°±0.5°)
	B		12°30'±30' (12.50°±0.5°)
	C		2°45'±30' (2.75°±0.5°)
	D		32°20'±0° (32.33°±0°)
	E+F		0°00'±6' (0°±0.1°)
		G-H mm (in.)	0±1 (0±0.04)

	Australia	185R14C	325 (3.25, 47) 350 (3.50, 51)*2
		195/70R15C	325 (3.25, 47) 350 (3.50, 51)*2
Others		Please refer to the Owner's Manual. (Section 8. SPECIFICATIONS)	
kPa (kgf/cm² or bar, psi)			