

LUBRICANT

Item			Capacity			Classification
			Liters	US qts	Imp. qts	
Manual transmission oil						API GL-4 or GL-5, SAE 75W-90
2WD (4-speed)			2.4	2.5	2.1	
2WD (5-speed)			2.2	2.3	1.9	
4WD			2.6	2.7	2.3	
Automatic transmission fluid						ATF DEXRON® II
Dry fill			6.5	6.9	5.7	
Drain and refill			2.4	2.5	2.1	
Transfer oil			1.2	1.3	1.1	API GL-4 or GL-5, SAE 75W-90
Differential oil	Front (4WD)		1.6	1.7	1.4	API GL-5 Above –18°C (0°F) SAE 90 Below –18°C (0°F) SAE 80W or 80W-90
	Rear	w/o LSD	2.2	2.3	1.9	API GL-5 Above –18°C (0°F) SAE 90 Below –18°C (0°F) SAE 80W or 80W-90
		w/ LSD	2.2	2.3	1.9	API GL-5 for LSD Above –18°C (0°F) SAE 90 Below –18°C (0°F) SAE 80W or 80W-90
Power steering fluid						ATF DEXRON®II
Gear box			1.0	1.1	0.9	
Brake fluid			–			SAE J1703 or FMVSS No.116 DOT3

