

# SUSPENSION AND AXLE

## SERVICE DATA

SS00D-03

	Tire size		kPa(kgf/cm <sup>2</sup> , psi)
	Front	Rear	
Cold tire inflation Pressure (Thai)	185R14-6LT	185R14-6LT	325 (3.25, 47)
	185R14-8LT	185R14-8LT	325 (3.25, 47)
	185R14-6LT	185R14-8LT	450 (4.50, 65)
	185R14C	185R14C	325 (3.25, 47)
	185R14C	185R14C	450 (4.50, 65)
	195/70R15C	195/70R15C	325 (3.25, 47)
	195/70R15C	195/70R15C	350 (3.50, 51)
	(RZH113R)		
	6.00-14LT	6.00-14LT	350 (3.50, 51)
	6.00-14LT	6.00-14LT	425 (4.25, 62)
	(LH172R)		
	6.00-14LT	6.00-14LT	375 (3.75, 54)
	6.00-14LT	6.00-14LT	425 (4.25, 62)
Cold tire inflation Pressure (Singapore)	185R14-6LT	185R14-6LT	350 (3.50, 51)
	185R14-8LT	185R14-8LT	350 (3.50, 51)
	185R14-8LT	185R14-8LT	450 (4.50, 65)
	185R14-6LT	185R14-8LT	350 (3.50, 51)
	185R14-8LT	185R14-8LT	450 (4.50, 65)
	185R14C	185R14C	350 (3.50, 51)
	185R14C	185R14C	450 (4.50, 65)
	195/70R15C	195/70R15C	350 (3.50, 51)
	195/70R15C	195/70R15C	450 (4.50, 65)
	195/70R15C	195/70R15C	450 (4.50, 65)
Cold tire inflation Pressure (Australia)	185R14C	185R14C	325 (3.25, 47)
	185R14C	185R14C	450 (4.50, 65)
	195/70R15C	195/70R15C	325 (3.25, 47)
	195/70R15C	195/70R15C	425 (4.25, 62)
Cold tire inflation Pressure (Russia)	185R14-8LT	185R14-8LT	325 (3.25, 47)
	185R14-8LT	185R14-8LT	450 (4.50, 65)
	185R14-6LT	185R14-8LT	325 (3.25, 47)
	185R14-8LT	185R14-8LT	450 (4.50, 65)
	185R14C	185R14C	325 (3.25, 47)
	185R14C	185R14C	450 (4.50, 65)
	195/70R15C	195/70R15C	325 (3.25, 47)
	195/70R15C	195/70R15C	450 (4.50, 65)
	195/75R16C	195/75R16C	300 (3.00, 44)
	195/75R16C	195/75R16C	375 (3.75, 54)

	Tire size		kPa(kgf/cm <sup>2</sup> , psi)	
	Front	Rear	Front	Rear
Cold tire inflation Pressure (The Middle East)	185R14-6LT	185R14-6LT	325 (3.25, 47)	350 (3.50, 51)
	185R14-8LT	185R14-8LT	325 (3.25, 47)	450 (4.50, 65)
	185R14-6LT	185R14-8LT	325 (3.25, 47)	450 (4.50, 65)
	185R14C	185R14C	350 (3.50, 51)	450 (4.50, 65)
	(For G. C. C. countries)			
	195/70R15C	195/70R15C	325 (3.25, 47)	450 (4.50, 65)
	(Except G. C. C. countries)			
	195/70R15C	195/70R15C	325 (3.25, 47)	425 (4.25, 62)
Cold tire inflation Pressure (Others)	6.00-14LT	6.00-14LT	325 (3.25, 47)	425 (4.25, 62)
	185R14-6LT	185R14-6LT	325 (3.25, 47)	350 (3.50, 51)
	185R14-8LT	185R14-8LT	325 (3.25, 47)	450 (4.50, 65)
	185R14-6LT	185R14-8LT	325 (3.25, 47)	450 (4.50, 65)
	185R14C	185R14C	325 (3.25, 47)	450 (4.50, 65)
	195/70R15C	195/70R15C	325 (3.25, 47)	425 (4.25, 62)
	6.00-14LT	6.00-14LT	350 (3.50, 51)	425 (4.25, 62)
Vehicle height (2WD)	Model	Tire size	Front* <sup>1</sup>	Rear* <sup>2</sup>
	RZH105L-BFMREX	185R14C	268 mm (10.55 in.)	286 mm (11.26 in.)
		195/70R15C	271 mm (10.67 in.)	287 mm (11.30 in.)
	RZH115L-BRMREX	185R14C	277 mm (10.91 in.)	285 mm (11.22 in.)
		195/70R15C	280 mm (11.02 in.)	286 mm (11.26 in.)
	LH113L-EBMRSX	195/70R15C	276 mm (10.87 in.)	291 mm (11.46 in.)
	LH105L-BFMRSX	195/70R15C	271 mm (10.67 in.)	285 mm (11.22 in.)
	LH115L-BRMRSX	195/70R15C	277 mm (10.91 in.)	286 mm (11.26 in.)
	RZH103R-RBMREQ	185R14C	273 mm (10.75 in.)	287 mm (11.30 in.)
		195/70R15C	282 mm (11.10 in.)	293 mm (11.54 in.)
	RZH103R-RBPREQ	185R14C	273 mm (10.75 in.)	287 mm (11.30 in.)
		195/70R15C	282 mm (11.10 in.)	293 mm (11.54 in.)
	RZH113R-RBMREQ	185R14C	273 mm (10.75 in.)	287 mm (11.30 in.)
		195/70R15C	282 mm (11.10 in.)	293 mm (11.54 in.)
	RZH113R-RBPREQ	185R14C	273 mm (10.75 in.)	287 mm (11.30 in.)
		195/70R15C	282 mm (11.10 in.)	293 mm (11.54 in.)

\*1: Front measuring point

Ground clearance of lower arm adjusting cam bolt center.

\*2: Rear measuring point

Leaf spring type rear suspension: Ground clearance of rear leaf spring front bushing center.

4 link type rear suspension: Ground clearance of lower control arm front bushing center.

## SERVICE SPECIFICATIONS – SUSPENSION AND AXLE

	Model	Tire size	Front*1	Rear*2
Vehicle height (2WD)	RZH125R-ZRMREQ	185R14C	266 mm (10.47 in.)	273 mm (10.75 in.)
		195/70R15C	275 mm (10.83 in.)	279 mm (10.98 in.)
	RZH125R-ZRPREQ	185R14C	266 mm (10.47 in.)	273 mm (10.75 in.)
		195/70R15C	275 mm (10.83 in.)	279 mm (10.98 in.)
	LH103R-RBMRSQ	185R14C	266 mm (10.47 in.)	287 mm (11.30 in.)
		195/70R15C	275 mm (10.83 in.)	293 mm (11.54 in.)
	LH103R-RBPRSQ	185R14C	266 mm (10.47 in.)	287 mm (11.30 in.)
		195/70R15C	275 mm (10.83 in.)	293 mm (11.54 in.)
	LH113R-RBMRSQ	185R14C	273 mm (10.75 in.)	287 mm (11.30 in.)
		195/70R15C	282 mm (11.10 in.)	293 mm (11.54 in.)
	LH113R-RBPRSQ	185R14C	273 mm (10.75 in.)	287 mm (11.30 in.)
		195/70R15C	282 mm (11.10 in.)	293 mm (11.54 in.)
	LH125R-ZRMRSQ	185R14C	266 mm (10.47 in.)	273 mm (10.75 in.)
		195/70R15C	275 mm (10.83 in.)	279 mm (10.98 in.)
	LH125R-ZRPRSQ	185R14C	266 mm (10.47 in.)	273 mm (10.75 in.)
		195/70R15C	275 mm (10.83 in.)	279 mm (10.98 in.)
	RZH113L-RBMRSV	185R14C	280 mm (11.02 in.)	301 mm (11.85 in.)
		195/70R15C	289 mm (11.38 in.)	307 mm (12.09 in.)
	RZH113L-SBMRSV	185R14C	287 mm (11.30 in.)	301 mm (11.85 in.)
		195/70R15C	296 mm (11.65 in.)	307 mm (12.09 in.)
	RZH113L-SRMRSV	185R14C	280 mm (11.02 in.)	294 mm (11.57 in.)
		195/70R15C	289 mm (11.38 in.)	300 mm (11.81 in.)
	RZH105L-BFMRSV	185R14C	266 mm (10.47 in.)	294 mm (11.57 in.)
		195/70R15C	275 mm (10.83 in.)	300 mm (11.81 in.)
	RZH115L-BRMRSV	185R14C	273 mm (10.75 in.)	287 mm (11.30 in.)
		195/70R15C	282 mm (11.10 in.)	293 mm (11.54 in.)
	LH113L-SBMRSV	185R14C	280 mm (11.02 in.)	294 mm (11.57 in.)
		195/70R15C	289 mm (11.38 in.)	300 mm (11.81 in.)
	LH115L-BRMRSV	185R14C	280 mm (11.02 in.)	287 mm (11.30 in.)
		195/70R15C	289 mm (11.38 in.)	293 mm (11.54 in.)
	RZH102L-RGMGS	185R14C	253 mm (9.96 in.)	280 mm (11.02 in.)
		195/70R15C	256 mm (10.08 in.)	281 mm (11.06 in.)
	RZH103L-RGMGS	185R14C	280 mm (11.02 in.)	301 mm (11.85 in.)
		195/70R15C	289 mm (11.38 in.)	307 mm (12.09 in.)
	RZH103R-RGMDE	185R14C	273 mm (10.75 in.)	301 mm (11.85 in.)
		195/70R15C	282 mm (11.10 in.)	307 mm (12.09 in.)
	RZH102R-SBMRS	6.00-14LT	290 mm (11.42 in.)	314 mm (12.36 in.)
		185R14C	273 mm (10.75 in.)	301 mm (11.85 in.)
		195/70R15C	282 mm (11.10 in.)	307 mm (12.09 in.)
	RZH102L-SBMRS	6.00-14LT	290 mm (11.42 in.)	314 mm (12.36 in.)
		185R14C	273 mm (10.75 in.)	301 mm (11.85 in.)
		195/70R15C	282 mm (11.10 in.)	307 mm (12.09 in.)
	RZH102L-RRMRS	6.00-14LT	290 mm (11.42 in.)	307 mm (12.09 in.)
		185R14C	273 mm (10.75 in.)	294 mm (11.57 in.)
		195/70R15C	282 mm (11.10 in.)	300 mm (11.81 in.)

\*1: Front measuring point

Ground clearance of lower arm adjusting cam bolt center.

\*2: Rear measuring point

Leaf spring type rear suspension: Ground clearance of rear leaf spring front bushing center.

4 link type rear suspension: Ground clearance of lower control arm front bushing center.

Vehicle height (2WD)	Model	Tire size	Front*1	Rear*2
	RZH112R-RBMRS	6.00-14LT	297 mm (11.69 in.)	314 mm (12.36 in.)
		185R14C	280 mm (11.02 in.)	301 mm (11.85 in.)
		195/70R15C	289 mm (11.38 in.)	307 mm (12.09 in.)
	RZH112R-RRMRS	6.00-14LT	297 mm (11.69 in.)	307 mm (12.09 in.)
		185R14C	280 mm (11.02 in.)	294 mm (11.57 in.)
		195/70R15C	289 mm (11.38 in.)	300 mm (11.81 in.)
	RZH112L-RBMRS	6.00-14LT	297 mm (11.69 in.)	314 mm (12.36 in.)
		185R14C	280 mm (11.02 in.)	301 mm (11.85 in.)
		195/70R15C	289 mm (11.38 in.)	307 mm (12.09 in.)
	RZH112L-SRMRS	6.00-14LT	297 mm (11.69 in.)	307 mm (12.09 in.)
		185R14C	280 mm (11.02 in.)	294 mm (11.57 in.)
		195/70R15C	289 mm (11.38 in.)	300 mm (11.81 in.)
	RZH103R-SRMRE	6.00-14LT	290 mm (11.42 in.)	307 mm (12.09 in.)
		185R14C	273 mm (10.75 in.)	294 mm (11.57 in.)
		195/70R15C	282 mm (11.10 in.)	300 mm (11.81 in.)
	RZH113R-RBMRE	6.00-14LT	297 mm (11.69 in.)	314 mm (12.36 in.)
		185R14C	280 mm (11.02 in.)	301 mm (11.85 in.)
		195/70R15C	289 mm (11.38 in.)	307 mm (12.09 in.)
	RZH113R-RRMRE	6.00-14LT	297 mm (11.69 in.)	307 mm (12.09 in.)
		185R14C	280 mm (11.02 in.)	294 mm (11.57 in.)
		195/70R15C	289 mm (11.38 in.)	300 mm (11.81 in.)
	RZH113L-RBMRE	185R14C	287 mm (11.30 in.)	301 mm (11.85 in.)
		195/70R15C	296 mm (11.65 in.)	307 mm (12.09 in.)
	LH102L-RBMRS	6.00-14LT	290 mm (11.42 in.)	307 mm (12.09 in.)
		185R14C	273 mm (10.75 in.)	294 mm (11.57 in.)
		195/70R15C	282 mm (11.10 in.)	300 mm (11.81 in.)
	LH102L-RRMRS	6.00-14LT	290 mm (11.42 in.)	307 mm (12.09 in.)
		185R14C	273 mm (10.75 in.)	294 mm (11.57 in.)
		195/70R15C	282 mm (11.10 in.)	300 mm (11.81 in.)
	LH112R-RBMRS	6.00-14LT	297 mm (11.69 in.)	314 mm (12.36 in.)
		185R14C	280 mm (11.02 in.)	301 mm (11.85 in.)
		195/70R15C	289 mm (11.38 in.)	307 mm (12.09 in.)
	LH112R-RRMRS	6.00-14LT	297 mm (11.69 in.)	307 mm (12.09 in.)
		185R14C	280 mm (11.02 in.)	294 mm (11.57 in.)
		195/70R15C	289 mm (11.38 in.)	300 mm (11.81 in.)
	LH112L-RBMRS	6.00-14LT	297 mm (11.69 in.)	314 mm (12.36 in.)
		185R14C	280 mm (11.02 in.)	301 mm (11.85 in.)
		195/70R15C	289 mm (11.38 in.)	307 mm (12.09 in.)
	LH112L-SRMRS	6.00-14LT	297 mm (11.69 in.)	307 mm (12.09 in.)
		185R14C	280 mm (11.02 in.)	294 mm (11.57 in.)
		195/70R15C	289 mm (11.38 in.)	300 mm (11.81 in.)
	LH103R-RBMRS	185R14LT	280 mm (11.02 in.)	301 mm (11.85 in.)
		195/70R15C	289 mm (11.38 in.)	307 mm (12.09 in.)
	LH103R-SBMRS	6.00-14LT	290 mm (11.42 in.)	307 mm (12.09 in.)
		185R14C	273 mm (10.75 in.)	294 mm (11.57 in.)
		195/70R15C	282 mm (11.10 in.)	300 mm (11.81 in.)

\*1: Front measuring point

Ground clearance of lower arm adjusting cam bolt center.

\*2: Rear measuring point

Leaf spring type rear suspension: Ground clearance of rear leaf spring front bushing center.

4 link type rear suspension: Ground clearance of lower control arm front bushing center.

## SERVICE SPECIFICATIONS – SUSPENSION AND AXLE

Vehicle height (2WD)	Model	Tire size	Front*1	Rear*2
	LH103R-SRMRS	6.00-14LT 185R14C 195/70R15C	290 mm (11.42 in.) 273 mm (10.75 in.) 282 mm (11.10 in.)	307 mm (12.09 in.) 294 mm (11.57 in.) 300 mm (11.81 in.)
	LH113R-RBMRS	6.00-14LT 185R14C 195/70R15C	297 mm (11.69 in.) 280 mm (11.02 in.) 289 mm (11.38 in.)	307 mm (12.09 in.) 294 mm (11.57 in.) 300 mm (11.81 in.)
	LH113R-RRMRS	6.00-14LT 185R14C 195/70R15C	290 mm (11.42 in.) 273 mm (10.75 in.) 282 mm (11.10 in.)	307 mm (12.09 in.) 294 mm (11.57 in.) 300 mm (11.81 in.)
	LH113L-RBMRS	6.00-14LT 185R14C 195/70R15C	290 mm (11.42 in.) 273 mm (10.75 in.) 282 mm (11.10 in.)	307 mm (12.09 in.) 294 mm (11.57 in.) 300 mm (11.81 in.)
	LH172R-RBMRS	6.00-14LT 185R14C 195/70R15C	297 mm (11.69 in.) 280 mm (11.02 in.) 289 mm (11.38 in.)	307 mm (12.09 in.) 294 mm (11.57 in.) 300 mm (11.81 in.)
	LH172R-RBMNS	6.00-14LT 185R14C 195/70R15C	297 mm (11.69 in.) 280 mm (11.02 in.) 289 mm (11.38 in.)	307 mm (12.09 in.) 294 mm (11.57 in.) 300 mm (11.81 in.)
	LH172R-RRMRS	185R14C 195/70R15C	273 mm (10.75 in.) 282 mm (11.10 in.)	294 mm (11.57 in.) 300 mm (11.81 in.)
	RZH114L-BFMGS	185R14C 195/70R15C	266 mm (10.47 in.) 275 mm (10.83 in.)	283 mm (11.38 in.) 289 mm (11.38 in.)
	RZH115L-BFMGS	195/70R15C	289 mm (11.38 in.)	293 mm (11.54 in.)
	LH174L-BFMGS	195/70R15C	258 mm (10.16 in.)	277 mm (10.91 in.)
	RZH104R-BFMRS	185R14C 195/70R15C	266 mm (10.47 in.) 275 mm (10.83 in.)	287 mm (11.30 in.) 293 mm (11.54 in.)
	RZH104L-BFMRS	185R14C 195/70R15C	266 mm (10.47 in.) 275 mm (10.83 in.)	294 mm (11.57 in.) 300 mm (11.81 in.)
	RZH104L-BFMNS	185R14C 195/70R15C	266 mm (10.47 in.) 275 mm (10.83 in.)	294 mm (11.57 in.) 300 mm (11.81 in.)
	RZH114R-BRMRS	185R14C 195/70R15C	280 mm (11.02 in.) 289 mm (11.38 in.)	287 mm (11.30 in.) 293 mm (11.54 in.)
	RZH114L-BRMRS	185R14C 195/70R15C	280 mm (11.02 in.) 289 mm (11.38 in.)	287 mm (11.30 in.) 293 mm (11.54 in.)
	RZH114L-ZRMRS	185R14C 195/70R15C	280 mm (11.02 in.) 289 mm (11.38 in.)	287 mm (11.30 in.) 293 mm (11.54 in.)
	RZH114L-ZRMNS	185R14C 195/70R15C	280 mm (11.02 in.) 289 mm (11.38 in.)	287 mm (11.30 in.) 293 mm (11.54 in.)
	RZH105L-BFMNS	185R14C 195/70R15C	266 mm (10.47 in.) 275 mm (10.83 in.)	294 mm (11.57 in.) 300 mm (11.81 in.)
	RZH115L-BRMRS	185R14C 195/70R15C	280 mm (11.02 in.) 289 mm (11.38 in.)	287 mm (11.30 in.) 293 mm (11.54 in.)
	LH104L-BFMRS	185R14C 195/70R15C	273 mm (10.75 in.) 282 mm (11.10 in.)	273 mm (10.75 in.) 279 mm (10.98 in.)

\*1:Front measuring point

Ground clearance of lower arm adjusting cam bolt center.

\*2: Rear measuring point

Leaf spring type rear suspension: Ground clearance of rear leaf spring front bushing center.

4 link type rear suspension: Ground clearance of lower control arm front bushing center.

	Model	Tire size	Front* <sup>1</sup>	Rear* <sup>2</sup>
	LH114R-BRMRS	185R14C 195/70R15C	280 mm (11.02 in.) 289 mm (11.38 in.)	287 mm (11.30 in.) 293 mm (11.54 in.)
Vehicle height (2WD)	LH114L-BRMRS	185R14C 195/70R15C	280 mm (11.02 in.) 289 mm (11.38 in.)	287 mm (11.30 in.) 293 mm (11.54 in.)
	LH115R-BRMRS	185R14C 195/70R15C	280 mm (11.02 in.) 289 mm (11.38 in.)	287 mm (11.30 in.) 293 mm (11.54 in.)
	LH115L-BRMRS	185R14C 195/70R15C	280 mm (11.02 in.) 289 mm (11.38 in.)	287 mm (11.30 in.) 293 mm (11.54 in.)
	LH184R-JRMNS	195/70R15C	289 mm (11.38 in.)	293 mm (11.54 in.)
	LH184R-ZRMNS	195/70R15C	289 mm (11.38 in.)	293 mm (11.54 in.)
	RZH153R-RBMNE	195/70R15C	250 mm (9.84 in.)	274 mm (10.79 in.)
	RZH135R-JFMGE	195/70R15C	258 mm (10.16 in.)	277 mm (10.91 in.)
Vehicle height (4WD)	LH166L-BFMRSX	195/70R16C	250 mm (9.84 in.)	314 mm (12.36 in.)
	LH176-BRMRSX	195/70R16C	260 mm (10.24 in.)	315 mm (12.40 in.)

\*<sup>1</sup>: Front measuring point

Ground clearance of lower arm adjusting cam bolt center.

\*<sup>2</sup>: Rear measuring point

Leaf spring type rear suspension: Ground clearance of rear leaf spring front bushing center.

4 link type rear suspension: Ground clearance of lower control arm front bushing center.

Front wheel alignment (2WD)	Camber	
	RZH103R, LH103R, RZH113R, LH113R, RZH125R, LH125R (Australia)	-0°15' ± 30' (-0.25° ± 0.5°)
	RZH102, RZH103, LH102, LH103, LH113L-EBMRSX, RZH114, RZH115, LH114, LH115	-0°20' ± 30' (-0.33° ± 0.5°)
	RZH112, RZH113, LH112, LH113, LH172, LH184	-0°25' ± 30' (-0.42° ± 0.5°)
	RZH102L-RGMGS, LH174L-BFMGS	-0°05' ± 30' (-0.08° ± 0.5°)
	RZH104, RZH105, LH104, LH105	-0°15' ± 30' (-0.25° ± 0.5°)
	RZH114L-BFMGS	-0°10' ± 30' (-0.17° ± 0.5°)
Front wheel alignment (4WD)	LH166L, LH176L	0°00' ± 30' (0.00° ± 0.5°)
Front wheel alignment (2WD)	Caster	
	RZH103R, LH103R (Australia)	1°20' ± 30' (1.33° ± 0.5°)
	RZH113R, LH113R (Australia)	1°25' ± 30' (1.42° ± 0.5°)
	RZH125R, LH125R (Australia)	1°50' ± 30' (1.83° ± 0.5°)
	RZH102, RZH103, LH102, LH103	0°55' ± 30' (0.92° ± 0.5°)      1°05' ± 30' (1.08° ± 0.5°)* <sup>3</sup>
	RZH112, RZH113, LH112, LH113	1°05' ± 30' (1.08° ± 0.5°)      1°10' ± 30' (1.17° ± 0.5°)* <sup>3</sup>
	RZH102L-RGMGS, RZH114, RZH115, LH114, LH115	1°25' ± 30' (1.42° ± 0.5°)
	LH113L-EBMRSX, RZH104, RZH105, LH104, LH105, LH172	1°20' ± 30' (1.33° ± 0.5°)
	RZH114L-BFMGS	1°35' ± 30' (1.58° ± 0.5°)
Front wheel alignment (4WD)	LH174L-BFMGS, LH184	1°40' ± 30' (0.67° ± 0.5°)
	Caster	
	LH166L, LH176L	2°55' ± 30' (2.92° ± 0.5°)

\*<sup>3</sup>: Bias tire

## SERVICE SPECIFICATIONS – SUSPENSION AND AXLE

Front wheel alignment (2WD)	Steering axis inclination		
	RZH103R, LH103R, RZH113R, LH113R, RZH125R, LH125R (Australia)		$10^{\circ}45' \pm 30'$ ( $10.75^{\circ} \pm 0.5^{\circ}$ )
	RZH102, RZH103, LH102, LH103, LH113L-EBMRSX, RZH114, RZH115, LH114, LH115		$10^{\circ}50' \pm 30'$ ( $10.83^{\circ} \pm 0.5^{\circ}$ )
	RZH112, RZH113, LH112, LH113, LH172, LH184		$10^{\circ}55' \pm 30'$ ( $10.92^{\circ} \pm 0.5^{\circ}$ )
	RZH104, RZH105, RZH114L-BFMGS		$10^{\circ}45' \pm 30'$ ( $10.75^{\circ} \pm 0.5^{\circ}$ )
Front wheel alignment (4WD)	LH166L, LH176L		$12^{\circ}35' \pm 30'$ ( $12.58^{\circ} \pm 0.5^{\circ}$ )
Front wheel alignment (2WD)	Toe-in (Total)		
	RZH103R, LH103R, RZH113R, LH113R, RZH125R, LH125R (Australia)		$0^{\circ}12' \pm 6'$ ( $2 \pm 1$ mm, $0.08 \pm 0.04$ in.)
	RZH102, RZH103, LH102, LH103, RZH112, RZH113, LH112, LH113, LH113L-EBMRSX, LH172, RZH114, RZH115, LH184		$0^{\circ}18' \pm 6'$ ( $3 \pm 1$ mm, $0.12 \pm 0.04$ in.)
	RZH104, RZH105, LH104, LH105, RZH114L-BFMGS		$0^{\circ}12' \pm 6'$ ( $2 \pm 1$ mm, $0.08 \pm 0.04$ in.)
	RZH102L-RGMGS, LH174L-BFMGS		$0^{\circ}06' \pm 6'$ ( $1 \pm 1$ mm, $0.04 \pm 0.04$ in.)
Front wheel alignment (4WD)	LH166L, LH176L		$00^{\circ}0' \pm 6'$ ( $0 \pm 1$ mm, $0.00 \pm 0.04$ in.)
Rear axle	Axle shaft hub bearing backlash	Maximum	0.7 mm (0.027 in.)
	Axle shaft runout	Maximum	2.0 mm (0.079 in.)
	Axle shaft flange runout	Maximum	0.1 mm (0.004 in.)