

TORQUE SPECIFICATION

Part Tightened	N·m	kgf·cm	ft·lbf
Hub Nut	100	1,050	76
Front Axle Hub Adjusting Nut	See page SA-7		
Front Axle Hub Lock Nut	47	480	35
Flange X Front Axle Hub	30	310	22
Drive Shaft Set Bolt	18	185	13
Brake Caliper X Flexible Hose	30	310	22
Brake Caliper Installation Bolt	103	1,050	76
Axle Hub X Disc	61	625	45
Knuckle Stopper Bolt	44	450	33
Steering Knuckle X Upper Suspension Arm	145	1,450	105
Steering Knuckle X Steering Knuckle Arm	160	1,660	120
Steering Knuckle Arm X Tie Rod End	91	930	67
Steering Knuckle X Lower Ball Joint	57	590	43
Brake Dust Cover Set Bolt	19	195	14
Rear Axle Housing X Bearing Case	6.9	700	51
ABS Speed Sensor X Rear Axle Housing	8.0	82	71 in. lbf
Brake Line	15	155	11
Shock Absorber X Axle Housing	39	400	29
Lateral Control Rod X Body	91	925	67
Upper Control Arm X Body	185	1,900	65
Upper Control Arm X Axle Housing	185	1,900	65
Lower Control Arm X Body	185	1,900	65
Lower Control Arm X Axle Housing	185	1,900	65
Lateral Control Rod X Axle Housing	105	1,100	80
Stabilizer Bar X Stabilizer Bar Link	48	490	36
Stabilizer Bar X Bracket	48	490	36
Stabilizer Bar Bracket X Body	72.6	740	54