

PROPELLER SHAFT**Specifications**

Spider axial play			Less than 0.05 mm (0.0020 in.)	
Spider bearing selection				
(2L engine A/T and 1RZ engine A/T)	Mark			
Bearing cup outer diameter	None	26.015 – 26.028 mm	1.0242 – 1.0247 in.	
	Red	26.036 – 26.049 mm	1.0250 – 1.0255 in.	
Bearing hole inner diameter	None	26.000 – 26.020 mm	1.0236 – 1.0244 in.	
	Drill	26.021 – 26.042 mm	1.0244 – 1.0253 in.	
(Others)	Mark			
Bearing cup outer diameter	None	29.008 – 29.021 mm	1.1420 – 1.1426 in.	
	Red	29.028 – 29.041 mm	1.1428 – 1.1433 in.	
Bearing hole inner diameter	None	29.000 – 29.020 mm	1.1417 – 1.1425 in.	
	Drill	29.021 – 29.042 mm	1.1426 – 1.1434 in.	
Snap ring thickness				
(2L engine A/T and 1RZ engine A/T)				
Color	Mark			
None	None	2.375 – 2.425 mm	0.0935 – 0.0955 in.	
Brown	None	2.425 – 2.475 mm	0.0955 – 0.0974 in.	
Blue	None	2.475 – 2.525 mm	0.0974 – 0.0994 in.	
(Others)	Color	Mark		
	None	1	2.100 – 2.150 mm	0.0827 – 0.0840 in.
	None	2	2.150 – 2.200 mm	0.0846 – 0.0866 in.
	None	3	2.200 – 2.250 mm	0.0866 – 0.0886 in.
	Brown	None	2.250 – 2.300 mm	0.0886 – 0.0906 in.
	Blue	None	2.300 – 2.350 mm	0.0906 – 0.0925 in.
	None	6	2.350 – 2.400 mm	0.0925 – 0.0945 in.
	None	7	2.400 – 2.450 mm	0.0945 – 0.0965 in.
	None	8	2.450 – 2.500 mm	0.0965 – 0.0984 in.
Runout	Limit	0.8 mm	0.031 in.	

Torque Specifications

Part tightened	kg-cm	ft-lb	N-m
Intermediate shaft x Propeller shaft	750	54	74
Intermediate shaft x Center bearing x Joint frange			
1st	1,850	134	181
2nd	Loosen nut		
3rd	700	51	69
Propeller shaft x Differential (2WD)	750	54	74
Propeller shaft x Transfer (4WD)	750	54	74
Propeller shaft x Differential (4WD)	750	54	74
Center bearing support (2WD) x Body	370	27	36
Stabilizer bar bracket	185	13	18